

# FD1604S/FD1604E-C1

## 4/4+4 PON PORTS GPON OLT



**Dedicated Chip**



**Layer3 Switching**



**Software Customization**



**USB Interface**

### Brief Views

GPON OLT FD1604S/FD1604E-C1 completely meets relative standard of ITU-T G.984.x/G.988, which is 1U rack-mounted device with 1 USB interface, 4 uplink GE ports, 4 uplink SFP ports, 2 10GE uplink ports. FD1604S-C1 has 4 fixed GPON ports and FD1604E-C1 has 4 fixed GPON ports and 1 4GPON port service card (optional). Each GPON port supports the splitting ratio of 1:128. The GPON system supports up to 512/1024 terminal connections.

FD1604E-C1 supports a pluggable service card, which is convenient and flexible to use, easy to deploy, and convenient for the subsequent expansion of network services. Moreover, the product meets the requirements of promoting network performance, improving reliability and reducing power consumption in the perspective of access network and enterprise network and is applicable to three-in-one broadcast television network, FTTP (Fiber to the premise), video monitoring network, enterprise LAN (Local Area Network), internet of things and other network applications with a very high price/performance ratio.

**FD1604S-C1**




**FD1604E-C1**



## Functional Feature

- Meet ITU-T G.984/G.988 standard and standards of Chinese Communication Industry
- Support OMCI Protocol
- 1U height 8PON OLT product in compact design of Pizza-Box
- Fan speed adjust automatically
- 1+1 Pluggable power module
- Complete PON protection switching function
- Layer 2 Switching Function
- OLT equips with very powerful layer 2 Full Wire Speed Switching and completely supports layer 2 protocol. OLT supports varieties of layer 2 functions like TRUNK, VLAN, LACP, rate limit, port isolate, queue technology, flow control technology, ACL and so on, which provides technical guarantee for the development of multi-service integrated.
- QoS Guarantee
- GPON Products maintains fully-improved DBA with excellent QoS service capabilities. DBA meets different QoS requirements from different service flow in latency, jitter, packet loss rate.
- Easy-to-Use Management System
- Support management method of CLI, WEB, SNMP, TELNET, SSH and meet OMCI standard, through OMCI channel protocol service management can be realized, including ONT function parameter set, T-CONT service lines and amount, QoS parameters, configuration information request, performance statistics, auto-reporting of running events in system, configuration for ONT from OLT, fault diagnosis and management of performance and safety.

## Product Interface and LED



Note: Take FD1604E-C1 as an example



# Product Specification

Mechanics			
Dimensions	440mm(L)*293mm(W)*44mm(H)		
Weight	3.6Kg (FD1604S-C1) 3.0Kg (FD1604E-C1)		
Hardware			
Uplink Port	COMBO port	4* 10/100/1000M auto-negotiation Ethernet ports	
		4* SFP interfaces	
PON Port	10-Gigabit	2* SFP+ interfaces	
	Quantity	4 (FD1604S-C1)	
		4/8 (FD1604E-C1)	
	Physical Interface	SFP slot	
	Interface Type	GPON: ITU-TG.984.2 Class B+/Class C+/Class C++	
Management Port	Max Splitting Ratio	GPON: 1:128	
		1* 100/1000BASE-Tx out-band Ethernet port	
		1* CONSOLE local management port	
USB Port		1* USB interface (It's used to backup configuration, upgrade program and record log information)	
PON Port Attribute	Transmission Distance	20KM	
	Port Rate	GPON: Downstream: 2.5Gbps Upstream: 1.25Gbps	
	Wavelength	Forwarding: 1490nm Receiving: 1310nm	
	Interface Type	SC/UPC	
	Fiber type	9/125 $\mu$ m SMF (Single Mode Fiber)	
	Light Transmission Power	Class B+: +1.5 ~ +5dBm	Class C+: +3 ~ +7dBm
	Receiving Sensitivity	Class B+: -28dBm	Class C+: -30dBm
	Saturation Power	Class B+: -8dBm	Class C+: -12dBm
Network Management Method		Support CLI, SNMP, TELNET, SSH, WEB	
Business Capabilities		Support device log, device upgrade, device management, condition monitoring, configuration management, and user management. Layer 2 switching configuration management: Like port management, VLAN, RSTP, IGMP, ACL, QoS and so on. PON function configuration management: Like OLT authentication, DBA template, service template, line template and so on. Layer 3 function: support static routing, dhcp-relay and vlanif configuration.	
Backplane Bandwidth		63G (FD1604S-C1) 78G (FD1604E-C1)	



## Power supply

AC	100V ~ 240V, 47 ~ 63Hz
DC	-40V ~ -72V
BBU (Backup Battery Unit)	DC: 11V~14V. Function: When the regular power supply is cut off, it can be switched to the backup power supply, and when the regular power supply resumes, it will switch back to the regular power supply and charge the backup power supply.
Maximum Power	34.6W (FD1604S-C1) 49W (FD1604E-C1)

## Environment

Working Temperature	-15 ~ 50°C
Storage Temperature	-40 ~ 85°C
Ambient Humidity	5 ~ 90% (Non-condensing)

**Copyright © Shenzhen C-Data Technology Co., Ltd. 2025. All rights reserved.**

Without the prior written consent of C-DATA, any reproduction, excerpting, backup, modification, translation or any other form of commercial use of this document or any portion of this document, and in any form or by any means, to transmit the document are prohibited.

